

Changes: RASMA2F and TIBAG2F are the correct ident. Inclusion of FI-D 05 and FI-D18

ARRIVAL RWY32 WEST TABULAR DESCRIPTION

NAV Spec	RNP 1	RNP1	RNP 1	RNP 1	RNP 1	RNP 1	RNP 1		NAV Spec	RNP 1	NAV Spec	RNP 1	RNP 1	RNP 1	RNP 1	RNP 1	RNP 1	RNP 1						
VPA/TCH									VPA/TCH								VPA/TCH							
Speed (kts)									Speed (kts)								Speed (kts)							
Altitude		+FL130			+FL080		+3600		Altitude		+FL130			+FL080		+3600	Altitude		+FL130			+FL080		+3600
Turn direction							_		Turn direction							_	Turn direction							
Distance (NM)		133.2	10.3	10.6	7.0	13.1	5.0		Distance (NM)		141.6	10.3	10.6	7.0	13.1	5.0	nce							_
Ļ		175.68	159.97	116.90	116.84	116.80	27.83		Ť		136.62	159.97	116.90	116.84	116.80	27.83	Distance (NM)		70.2	10.3	-	1 7.0	13.1	+
° S	1	194 1	178 1	135 1	135 1	135 1	46 2	-	° W _°	1	155 1	178 1	135 1	135 1	135 1	46 2	۰T		90.72	159.97	116.90	116.84	116.80	27.83
ຄູ	-18.38	-18.38	-18.38	-18.38	-18.38	-18.38	-18.38		סנ	-18.38	-18.38	-18.38	-18.38	-18.38	-18.38	-18.38	W°	i	109	178	135	135	135	46
Fly- Mag over Var	-18								Fly- Mag over Var	-18							Mag Var	-18.38	-18.38	-18.38	-18.38	-18.38	-18.38	-18.38
	1	z	z	Z	z	z	z		na ing marak		Z	z	Z	Z		z	Fly- over	\vdash	z	z	z	z	z	z
WPT Identifier	DUNRI	IMKOV	MP551	MP602	MP531	MP501	ESTEK		WPT Identifier	TIBAG	IMKOV	MP551	MP602	MP531	MP501	ESTEK	WPT I	A		MP551			\vdash	
Path Descriptor	Щ	TF	TF	TF	TF	TF	TF		Path Descriptor	Ŀ	TF	TF	TF	TF	TF	TF	Path V Descriptor Ic	+		TF			TF	TF
Serial number	10	20	30	40	50	60	70		Serial number	10	20	30	40	50	60	70	Serial F number [20 1					L 02
Route Designator				DI INR 1E					Route Designator				TIRA7F				Route Designator	-			RASM2F			

AD 2- FIMP – 37.2A 18 JUL 24

AIP Republic of Mauritius

	Path	WPT	Fly-	Mag	V V O	۲°	Distance	Turn	A 1414. A C	Speed	NAV
Designator number	er Descriptor	Identifier		Var	N		(MN)	direction	Alliude	(kts)	Spec
10	Щ	EPTEK		-18.38	4						RNP 1
20	11	MP551	z	-18.38	106	87.23	69.0				RNP 1
30	TF	MP602	z	-18.38	135	116.90 10.6	10.6				RNP 1
EF1E4	TF	MP531	z	-18.38	135	116.84 7.0	7.0		+FL080		RNP 1
50	TF	MP501	z	-18.38	135	116.80 13.1	13.1				RNP 1
60	TF	ESTEK	z	-18.38	46	27.83	5.0	_	+3600		RNP 1

NAV	Spec	RNP 1	RNP 1	RNP 1	RNP 1
VPA/TCH					
Speed	(kts)	142110 Back			
Altitude			+FL080		+3600
Turn	direction				Г
Distance	(MM)		75.4	13.1	5.0
T°			65.69		27.83
W°		-	84	135	46
Mag	Var	-18.38	-18.38	-18.38	-18.38
Fly-	over		z	z	z
WPT	Identifier	PASAR	MP531	MP501	ESTEK
Path	Descriptor	≝	TF	TF	TF
Serial	number	10	20	30	40
Route	Designator	5. (1) (1) (1) (1) (1) (1) (1) (1) (1) (1)	DACADE	LANCET	

TABULAR DESCRIPTION

No Change